

**PRODUCT
NEWS**

02/2021



Synthalat QUL 5120

Urethane oil


FIELDS OF APPLICATION

SYNTHALAT QUL 5120 is mainly suited for manufacturing solvent-based wood stains, clear coatings and other products for wood protection and wood care, especially for professional and semi-professional use.

SYNTHALAT QUL 5120 can be easily mixed with various medium and long oil alkyds and it can also be used as a blending resin in industrial paints (10-20%). Concerning the formulation of driers, we recommend the use of iron (OxyCoat 1130) or manganese (DriCat 2753 F / DriNate SG 160) in combination with Zr, Sr or Bi.

HIGHLIGHTS

- **Very good grain enhancement**
- **Excellent matting properties**
- **Solvent-free wood oils with fast drying can be produced**
- **Improvement of adhesion, salt-spray and condensation test on aluminium**



PROPERTIES AND TECHNICAL DATA

Supplied as	100 %
Viscosity/23°C	2000 – 3000 mPas
Acid value (in mg KOH/g)	max. 4
Colour value (iodine)	max. 12


SAMPLING

Ordering samples of **Synthalat QUL 5120** can be done easily on our website.

CONTACT

If you are interested in more information about our products please contact your known person in charge from the sales or research and development department or our headquarters directly under following references:

SYNTHOPOL DEUTSCHLAND
 Dr. rer. pol. Koch GmbH & Co. KG
 Alter Postweg 35
 21614 Buxtehude, Germany

Telephone: +49 (0) 4161/7071-0
 Telefax: +49 (0) 4161/80130

info@synthopol.com
www.synthopol.com

